

SPECIFICATIONS

| MODEL | | | SP38N2×14H | SP38N2×19H | SP67N2×27H | SP120N2×32H-MH |
|-------------------------------------|------------------|----|------------|------------|------------|----------------|
| S.I. RANGE [N · m] | | | 8~25 | 8~39 | 13~67 | 24~120 |
| METRIC RANGE [kgf · cm] | | | 80~250 | 80~390 | 130~670 | 240~1200 |
| WIDTH ACROSS FLATS [mm] | | | 14 | 19 | 27 | 32 |
| MINIMUM PIPING PITCH [mm] | | | 26 | 35 | 46 | 54 |
| MAX. HAND FORCE [N] | | | 148 | 227 | 277 | 385 |
| DIMENSION [mm] | EFFECTIVE LENGTH | L | 169 | 172 | 242 | 312 |
| | OVERALL LENGTH | L' | 218 | 222 | 294 | 363 |
| | HEAD | C | 26.3 | 33.1 | 43.6 | 51.6 |
| | | b | 8 | | 11 | 14 |
| | BODY | m | 25.5 | | 28 | |
| | | n | 11.2 | | 12.2 | |
| | | d | 20 | | 21.7 | |
| D | | 34 | | 21.5 | | |
| WEIGHT[kg] | | | 0.37 | | 0.48 | 0.75 |
| THRUSTING TOOL [OPTIONAL ACCESSORY] | | | No.930 | | | |

Accuracy ±3%

Notes

Models SP38N2X14H to SP67N2X27H come with a resin grip, while SP120N2X32H-MH has a metal grip.

DIMENSIONS

