

SPECIFICATIONS

Accuracy ± 3%

S.I. MODEL			LTD15CN		LTD30CN		LTD60CN		LTD120CN		LTD260CN	LTD500CN	LTD1000CN	LTD2000CN2		
TORQUE RANGE [cN · m]	MIN. ~ MAX.		2~15		4~30		10~60		20~120		60~260	100~500	200~1000	400~2000		
	GRAD.		0.1		0.2		0.5		1		2	5				
METRIC MODEL			1.5LTD		3LTD		6LTD		12LTD		26LTD	50LTD	100LTD	LTD200M2		
TORQUE RANGE [kgf · cm]	MIN. ~ MAX.		0.2~1.5		0.4~3		1~6		2~12		6~26	10~50	20~100	40~200		
	GRAD.		0.01		0.02		0.05		0.1		0.2	0.5				
AMERICAN MODEL			LTD20Z	LTD1.3I	LTD40Z	LTD2.6I	LTD80Z	LTD5I	LTD150Z	LTD10I	LTD22I	LTD40I	LTD90I	LTD180I LTD180I2		
TORQUE RANGE [ozf · in/lbf · in]	MIN. ~ MAX.		ozf · in 6~20	lbf · in 0.2~1.3	ozf · in 15~40	lbf · in 0.4~2.6	ozf · in 20~80	lbf · in 1~5	ozf · in 30~150	lbf · in 2~10	lbf · in 6~22	10~40	20~90	30~180 40~180		
	GRAD.		ozf · in 0.2	lbf · in 0.01	ozf · in 0.5	lbf · in 0.02	ozf · in 1	lbf · in 0.05	ozf · in 2	lbf · in 0.1	lbf · in 0.2	0.5				
APPLICABLE SCREW	SMALL SCREW		(M1.8)		M2 (M2.2)		M2.5, M3		(M3.5)		M4 (M4.5)	M5, M6	(M7)	M8		
	TAPPING SCREW		(M1.4) M1.6		(M1.8) M2		(M2.2) M2.5		M3 (M3.5)		M4	(M4.5)	M6	(M7)		
DIMENSION [mm]	OVERALL LENGTH	L'	100				110		130		150	155	185	255		
	GRIP	D1	16				20		24		30.5	33	43	48		
	BODY	D2	10.7				14.8		18		23	26	32	35		
		D3	11											12	25	
		L1	18				24								25	35
		L2	76.5~84.3				81.1~90.1		105~115		122.8~132.8	129~141	151~163	209.5~236		
	LOCKER	d	23.5				29		33		41	45				
		W	21.5				26.5		30		37.5	41				
WEIGHT [kg]			0.05				0.08		0.13		0.22	0.33	0.58	1.15		

Notes

Auxiliary tightening tool for LTD500CN and 1000CN is available (separately sold). LTD180I use special sized bits. LTD2000CN2, LTD200M2 and LTD180I2 version 2 now feature 1/4 square drive.

Standard accessories

Resin grip (for LTD120CN and LTD260CN models only) is a standard accessory.

LTD260CN Preset hook key for up to 2000CN models only.

LTD2000CN2, LTD200M2, LTD180I(2) have an auxiliary T-Handle tightening tool supplied as a standard accessory.

DIMENSIONS

